


RANA NEO 9500LM S 1500 840 SSC EM 2L WHITE

Item No: 0054269

SYLVANIA


PROTM



Surface or Suspended LED luminaire with Micro Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1447x187x56mm, White body colour, IP20, IK07, SylSmart Standalone capable, Emergency 3 hours, Low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 9500lm, 73W, 130lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.

Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Beam area [m²]	Beam flux [lm]	Beam illuminance [lx]
0.5	0.90	60.0°	0.90	0.64	2545	3975
1.0	1.79	60.0°	1.79	2.54	6371	1565
1.5	2.69	60.0°	2.69	3.81	2032	533
2.0	3.59	60.0°	3.59	5.07	1590	313
2.5	4.49	60.0°	4.49	6.34	1219	191
3.0	5.39	60.0°	5.39	7.61	1019	134
3.5	6.29	60.0°	6.29	8.88	888	100
4.0	7.19	60.0°	7.19	10.15	777	77
4.5	8.09	60.0°	8.09	11.42	688	60
5.0	8.99	60.0°	8.99	12.69	611	48
5.5	9.89	60.0°	9.89	13.96	545	39
6.0	10.79	60.0°	10.79	15.23	488	32
6.5	11.69	60.0°	11.69	16.50	439	26
7.0	12.59	60.0°	12.59	17.77	397	22
7.5	13.49	60.0°	13.49	19.04	361	19
8.0	14.39	60.0°	14.39	20.31	330	16
8.5	15.29	60.0°	15.29	21.58	303	14
9.0	16.19	60.0°	16.19	22.85	280	12
9.5	17.09	60.0°	17.09	24.12	260	11
10.0	17.99	60.0°	17.99	25.39	242	9
10.5	18.89	60.0°	18.89	26.66	226	8
11.0	19.79	60.0°	19.79	27.93	212	7
11.5	20.69	60.0°	20.69	29.20	199	6
12.0	21.59	60.0°	21.59	30.47	187	5
12.5	22.49	60.0°	22.49	31.74	176	5
13.0	23.39	60.0°	23.39	33.01	166	4
13.5	24.29	60.0°	24.29	34.28	157	4
14.0	25.19	60.0°	25.19	35.55	148	3
14.5	26.09	60.0°	26.09	36.82	140	3
15.0	26.99	60.0°	26.99	38.09	132	3
15.5	27.89	60.0°	27.89	39.36	125	3
16.0	28.79	60.0°	28.79	40.63	118	2
16.5	29.69	60.0°	29.69	41.90	112	2
17.0	30.59	60.0°	30.59	43.17	106	2
17.5	31.49	60.0°	31.49	44.44	101	2
18.0	32.39	60.0°	32.39	45.71	96	2
18.5	33.29	60.0°	33.29	46.98	91	2
19.0	34.19	60.0°	34.19	48.25	87	2
19.5	35.09	60.0°	35.09	49.52	83	2
20.0	35.99	60.0°	35.99	50.79	79	2
20.5	36.89	60.0°	36.89	52.06	76	2
21.0	37.79	60.0°	37.79	53.33	72	2
21.5	38.69	60.0°	38.69	54.60	69	2
22.0	39.59	60.0°	39.59	55.87	66	2
22.5	40.49	60.0°	40.49	57.14	63	2
23.0	41.39	60.0°	41.39	58.41	60	2
23.5	42.29	60.0°	42.29	59.68	57	2
24.0	43.19	60.0°	43.19	60.95	55	2
24.5	44.09	60.0°	44.09	62.22	52	2
25.0	44.99	60.0°	44.99	63.49	50	2
25.5	45.89	60.0°	45.89	64.76	48	2
26.0	46.79	60.0°	46.79	66.03	46	2
26.5	47.69	60.0°	47.69	67.30	44	2
27.0	48.59	60.0°	48.59	68.57	42	2
27.5	49.49	60.0°	49.49	69.84	40	2
28.0	50.39	60.0°	50.39	71.11	38	2
28.5	51.29	60.0°	51.29	72.38	36	2
29.0	52.19	60.0°	52.19	73.65	34	2
29.5	53.09	60.0°	53.09	74.92	32	2
30.0	53.99	60.0°	53.99	76.19	30	2
30.5	54.89	60.0°	54.89	77.46	28	2
31.0	55.79	60.0°	55.79	78.73	26	2
31.5	56.69	60.0°	56.69	80.00	24	2
32.0	57.59	60.0°	57.59	81.27	22	2
32.5	58.49	60.0°	58.49	82.54	20	2
33.0	59.39	60.0°	59.39	83.81	18	2
33.5	60.29	60.0°	60.29	85.08	16	2
34.0	61.19	60.0°	61.19	86.35	14	2
34.5	62.09	60.0°	62.09	87.62	12	2
35.0	62.99	60.0°	62.99	88.89	10	2
35.5	63.89	60.0°	63.89	90.16	8	2
36.0	64.79	60.0°	64.79	91.43	6	2
36.5	65.69	60.0°	65.69	92.70	4	2
37.0	66.59	60.0°	66.59	93.97	2	2
37.5	67.49	60.0°	67.49	95.24	1	2
38.0	68.39	60.0°	68.39	96.51	0	2
38.5	69.29	60.0°	69.29	97.78	0	2
39.0	70.19	60.0°	70.19	99.05	0	2
39.5	71.09	60.0°	71.09	100.32	0	2
40.0	71.99	60.0°	71.99	101.59	0	2
40.5	72.89	60.0°	72.89	102.86	0	2
41.0	73.79	60.0°	73.79	104.13	0	2
41.5	74.69	60.0°	74.69	105.40	0	2
42.0	75.59	60.0°	75.59	106.67	0	2
42.5	76.49	60.0°	76.49	107.94	0	2
43.0	77.39	60.0°	77.39	109.21	0	2
43.5	78.29	60.0°	78.29	110.48	0	2
44.0	79.19	60.0°	79.19	111.75	0	2
44.5	80.09	60.0°	80.09	113.02	0	2
45.0	80.99	60.0°	80.99	114.29	0	2
45.5	81.89	60.0°	81.89	115.56	0	2
46.0	82.79	60.0°	82.79	116.83	0	2
46.5	83.69	60.0°	83.69	118.10	0	2
47.0	84.59	60.0°	84.59	119.37	0	2
47.5	85.49	60.0°	85.49	120.64	0	2
48.0	86.39	60.0°	86.39	121.91	0	2
48.5	87.29	60.0°	87.29	123.18	0	2
49.0	88.19	60.0°	88.19	124.45	0	2
49.5	89.09	60.0°	89.09	125.72	0	2
50.0	89.99	60.0°	89.99	126.99	0	2
50.5	90.89	60.0°	90.89	128.26	0	2
51.0	91.79	60.0°	91.79	129.53	0	2
51.5	92.69	60.0°	92.69	130.80	0	2
52.0	93.59	60.0°	93.59	132.07	0	2
52.5	94.49	60.0°	94.49	133.34	0	2
53.0	95.39	60.0°	95.39	134.61	0	2
53.5	96.29	60.0°	96.29	135.88	0	2
54.0	97.19	60.0°	97.19	137.15	0	2
54.5	98.09	60.0°	98.09	138.42	0	2
55.0	98.99	60.0°	98.99	139.69	0	2
55.5	99.89	60.0°	99.89	140.96	0	2
56.0	100.79	60.0°	100.79	142.23	0	2
56.5	101.69	60.0°	101.69	143.50	0	2
57.0	102.59	60.0°	102.59	144.77	0	2
57.5	103.49	60.0°	103.49	146.04	0	2
58.0	104.39	60.0°	104.39	147.31	0	2
58.5	105.29	60.0°	105.29	148.58	0	2
59.0	106.19	60.0°	106.19	149.85	0	2
59.5	107.09	60.0°	107.09	151.12	0	2
60.0	107.99	60.0°	107.99	152.39	0	2
60.5	108.89	60.0°	108.89	153.66	0	2
61.0	109.79	60.0°	109.79	154.93	0	2
61.5	110.69	60.0°	110.69	156.20	0	2
62.0	111.59	60.0°	111.59	157.47	0	2
62.5	112.49	60.0°	112.49	158.74	0	2
63.0	113.39	60.0°	113.39	159.99	0	2
63.5	114.29	60.0°	114.29	161.24	0	2
64.0	115.19	60.0°	115.19	162.49	0	2
64.5	116.09	60.0°	116.09	163.74	0	2
65.0	116.99	60.0°	116.99	164.99	0	2
65.5	117.89	60.0°	117.89	166.24	0	2
66.0	118.79	60.0°	118.79	167.49	0	2
66.5	119.69	60.0°	119.69	168.74	0	2
67.0	120.59	60.0°	120.59	169.99	0	2
67.5	121.49	60.0°	121.49	171.24	0	2
68.0	122.39	60.0°	122.39	172.49	0	2
68.5	123.29	60.0°	123.29	173.74	0	2
69.0	124.19	60.0°	124.19	174.99	0	2
69.5	125.09	60.0°	125.09	176.24	0	2
70.0	125.99	60.0°	125.99	177.49	0	2
70.5	126.89	60.0°	126.89	178.74	0	2
71.0	127.79	60.0°	127.79	179.99	0	2
71.5	128.69	60.0°	128.69	181.24	0	2
72.0	129.59	60.0°	129.59	182.49	0	2
72.5	130.49	60.0°	130.49	183.74	0	2
73.0	131.39	60.0°	131.39	184.99	0	2
73.5	132.29	60.0°	132.29	186.24	0	2
74.0	133.19	60.0°	133.19	187.49	0	2
74.5	134.09	60.0°	134.09	188.74	0	2
75.0	134.99	60.0°	134.99	189.99	0	2
75.5	135.89	60.0°	135.89	191.24	0	2
76.0	136.79	60.0°	136.79	192.49	0	2
76.5	137.69	60.0°	137.69	193.74	0	2
77.0	138.59	60.0°	138.59	194.99	0	2
77.5	139.49	60.0°	139.49	196.24	0	2
78.0	140.39	60.0°	140.39	197.49	0	2
78.5	141.29	60.0°	141.29	198.74	0	2
79.0	142.19	60.0°	142.19	199.99	0	2
79.5	143.09	60.0°	143.09	201.24	0	2
80.0	143.99	60.0°	143.99	202.49	0	2
80.5	144.89	60.0°	144.89	203.74	0	2
81.0	145.79	60.0°	145.79	204.99	0	2
81.5	146.69	60.0°	146.69	206.24	0	2
82.0	147.59	60.0°	147.59	207.49	0	2
82.5	148.49	60.0°	148.49	208.74	0	2
83.0	149.39	60.0°	149.39	209.99	0	2
83.5	150.29	60.0°	150.29	211.24	0	2
84.0	151.19	60.0°	151.19	212.49	0	2
84.5	152.09	60.0°	152.09	213.74	0	2
85.0	152.99	60.0°	152.99	214.99	0	2
85.5	153.89	60.0°	153.89	216.24	0	2
86.0	154.79	60.0°	154.79	217.49	0	2
86.5	155.69	60.0°	155.69	218.74	0	2
87.0	156.59	60.0°	156.59	219.99	0	2
87.5	157.49	60.0°	157.49	221.24	0	2
88.0	158.39	60.0°	158.39	222.49	0	2
88.5	159.29	60.0°	159.29	223.74	0	2
89.0	160.19	60.0°	160.19	224.99	0	2
89.5	161.09	60.0°	161.09	226.24	0	2
90.0	161.99	60.0°	161.99	227.49	0	2
90.5	162.89	60.0°	162.89	228.74	0	2
91.0	163.79	60.0°	163.79	229.99	0	2
91.5	164.69	60.0°	164.69	231.24	0	2
92.0	165.59	60.0°	165.59	232.49	0	2
92.5						

RANA NEO 9500LM S 1500 840 SSC EM 2L WHITE

Item No: 0054269

SYLVANIA

General data

Product name	RANA NEO 9500LM S 1500 840 SSC EM 2L WHITE
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	5°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	9500
Luminaire efficacy (lm/W)	130
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	80

Electrical data

Emergency mode	Non-maintained
Emergency type	
Emergency duration (h)	3
Total power consumption (W)	80
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Standalone (SSC)
Minimum dimming level (%)	1
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Energy Efficiency Class (A->G) of contained light source	C, C(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	36
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	22
Max. products per 20A B Breaker	27
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

RANA NEO 9500LM S 1500 840 SSC EM 2L WHITE

Item No: 0054269



Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	96000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Not Applicable
Nominal Product Length (mm)	1440
Nominal Product Width (mm)	187
Nominal Product Height (mm)	47
Weight (kg)	3.9

Packaging

Product EAN number	5410288542690
Packaging single length / height (cm)	153.5
Packaging single width (cm)	6.5
Packaging single depth (cm)	21.0
DUN14 (inner)	05410288542690
Units per outer package	1
Packaging outer length / height (cm)	153.5
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	21.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	5-25