

CONTINUUM PLUS TR 0.6 940 CO UGR D DALI W

Item No: 2064508


Concord



CONTINUUM PLUS TR 0.6 940 CO UGR D DALI W is a linear luminaire with trim body for plasterboard ceilings, suitable for recessed installation either horizontally or vertically, recessed mounting accessory, direct light distribution, compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, white (RAL9016) finishing, extruded aluminium body, 605x80x85mm dimensions, prismatic diffuser combined with lenses, 4000K (neutral white) colour temperature, total system power: 11.5W, total fixture output: 1575lm, luminaire efficacy: 137lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 250mA, electronic driver, DALI dimmable, Class I electrical protection, IP20, IK03, suitable for internal environment only. The product is delivered without diffuser, end cap, suspension or power supply kit, the accessories eg rolled diffuser (2064607) to be ordered separately.

Technical Assets

Dimensions (mm)




Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Beam diameter [ft] | Illuminance [lx] |
|--------------|-------------------|-------------------|--------------------|------------------|
| 0.5 | 0.71 | 0.73 | 2.36 | 4096 |
| | | | 2.39 | 1540 |
| 1.0 | 1.42 | 1.46 | 4.78 | 1024 |
| | | | 4.78 | 396 |
| 1.5 | 2.12 | 2.19 | 7.17 | 544 |
| | | | 7.17 | 169 |
| 2.0 | 2.83 | 2.92 | 9.58 | 396 |
| | | | 9.58 | 81 |
| 2.5 | 3.54 | 3.65 | 11.97 | 196 |
| | | | 11.97 | 54 |
| 3.0 | 4.25 | 4.38 | 14.37 | 128 |
| | | | 14.37 | 36 |

Distance [m] Cone diameter [m] Beam diameter [m] Beam diameter [ft] Illuminance [lx]

— C0 - C180 (Half beam angle: 72.0°)
— C90 - C270 (Half beam angle: 70.0°)



CONTINUUM PLUS TR 0.6 940 CO UGR D DALI W

Item No: 2064508

Concord

General data

| | |
|----------------------------------|---|
| Product name | CONTINUUM PLUS TR 0.6 940 CO UGR D DALI W |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Ceiling recessed mounting |
| Built in presence detector | NONE |
| Fixture rating | Enclosed |
| General application | Office, Education, Retail |
| Operating temperature range (°C) | 1°C...+25°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002892 |
| Warranty | 5 years |

Optical data

| | |
|-----------------------------------|---------------|
| Fixture luminous flux (lm) | 1575 |
| Luminaire efficacy (lm/W) | 137 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Distribution type | Symmetric |
| Glare control | < 19 |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|--|-----------------------------|
| Emergency type | |
| Total power consumption (W) | 11.5 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.97 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 10 |
| Electrical protection | Class I |
| Control gear required | No |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI-2 |
| Minimum dimming level (%) | 1 |
| Drive current (mA) | 250 |
| Inrush Current (A) | 7.5 |
| Inrush Duration (µs) | 220 |
| Energy Efficiency Class (A->G) of contained light source | B |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Ultra low (5% or less) |
| Max. products per 10A C Breaker | 70 |
| Max. products per 13A C Breaker | 90 |
| Max. products per 16A C Breaker | 110 |
| Max. products per 20A C Breaker | 138 |
| Max. products per 10A B Breaker | 42 |
| Max. products per 13A B Breaker | 54 |
| Max. products per 16A B Breaker | 66 |
| Max. products per 20A B Breaker | 83 |
| Connectable conductor cross section - Min (mm ²) | 0.75 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

CONTINUUM PLUS TR 0.6 940 CO UGR D DALI W

Item No: 2064508

Concord

Lifetime data

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 89000 |

Physical data

| | |
|-----------------------------|----------------------------------|
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Transparent |
| Diffuser material | PC Polycarbonate |
| Reflector finish | Not Applicable |
| Nominal Product Length (mm) | 605 |
| Nominal Product Width (mm) | 80 |
| Nominal Product Height (mm) | 85 |
| Weight (kg) | 1.6 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5025768645084 |
| Packaging single length / height (cm) | 71.0 |
| Packaging single width (cm) | 11.7 |
| Packaging single depth (cm) | 14.7 |
| DUN14 (inner) | 05025768645084 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 71.0 |
| Packaging outer width (cm) | 11.7 |
| Packaging outer depth (cm) | 14.7 |

Safety data

| | |
|----------------------------------|------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | 1-25 |