


# Solstice 250 2400lm 940 SSA01D

Item No: 2070296


**Concord**



The Solstice 250 2400lm 940 SSA01D is a high efficient SSAdimmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 4000K Neutral White, Class II, Protection rating IP40/IP20, Cut out dimensions: 250mm.

## Technical Assets


### Dimensions (mm)



### Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Illuminance [lx]
0.5	0.78	Ø171	37.8"	859
1.0	1.56	Ø342	75.6"	429
1.5	2.34	Ø513	113.4"	286
2.0	3.11	Ø684	151.2"	215
2.5	3.89	Ø855	189.0"	172
3.0	4.67	Ø1026	226.8"	142

Distance [m] Cone diameter [m] Illuminance [lx]  
 CO - C180 (Half beam angle: 75.0°)



# Solstice 250 2400lm 940 SSA01D

Item No: 2070296

# Concord

## General data

Product name	Solstice 250 2400lm 940 SSA01D
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Built in presence detector	NONE
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	40
Virtual assistant compatibility	N/A
ETIM Class	EC001744
E-number FI	4275576
Warranty	5 years

## Optical data

Fixture luminous flux (lm)	2400
Luminaire efficacy (lm/W)	141
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	70
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

## Electrical data

Total power consumption (W)	17
Supply current (A)	20
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Connected (SSA)
Minimum dimming level (%)	1
Drive current (mA)	450
Inrush Current (A)	20
Inrush Duration (µs)	141
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	31
Max. products per 13A C Breaker	40
Max. products per 16A C Breaker	10
Max. products per 20A C Breaker	66
Max. products per 10A B Breaker	19
Max. products per 13A B Breaker	24
Max. products per 16A B Breaker	16
Max. products per 20A B Breaker	40
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.5
Connectable conductor cross section - Max (mm <sup>2</sup> )	2.5

# Solstice 250 2400lm 940 SSA01D

Item No: 2070296

Concord

## Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L80 B10	120000
Lifespan L90 B10	68000

## Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP54/20
IK rating	IK02
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Height (mm)	107
Nominal Product Diameter (mm)	266
Built-in diameter (mm)	250
Max. Lamp Diameter (mm) - D	266
Weight (kg)	1.8
Recessed Depth (mm)	150

## Packaging

Product EAN number	5025768702961
Packaging single length / height (cm)	33.5
Packaging single width (cm)	33.5
Packaging single depth (cm)	15.3
DUN14 (inner)	05025768702961
Units per outer package	1
Packaging outer length / height (cm)	33.5
Packaging outer width (cm)	33.5
Packaging outer depth (cm)	15.3

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-10-40