


Beacon XL Muse 3000K DALI L3 ST Adaptor White

Item No: 2692777


Concord



Integrated LED spotlight, white, unique soft-touch ring, adjustable beam angle from a 10 spot to a 70 flood, compact and minimalist design, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 10 spot to 70 flood, optics: aspheric glass lens, colour temperature: 3000K warm white, total system power: 41W, total fixture output: 2544lm, luminaire efficacy: 62lm/W, LOR: 100%, super high colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 1050mA, electronic driver, DALI dimmable, power factor: 0.95, Stucchi DALI Adaptor. Compatible with OneTrack (for detailed information please check the compatibility list).


Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Beam area [m²]	Illuminance [lx]
0.5	0.00	5.0°	0.00	0.00	4913
1.0	0.00	5.0°	0.00	0.00	1228
1.5	0.00	5.0°	0.00	0.00	545
2.0	0.00	5.0°	0.00	0.00	307
2.5	0.00	5.0°	0.00	0.00	195
3.0	0.00	5.0°	0.00	0.00	136



Beacon XL Muse 3000K DALI L3 ST Adaptor White

Item No: 2692777

Concord

General data

Product name	Beacon XL Muse 3000K DALI L3 ST Adaptor White
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Built in presence detector	NONE
Environment	Internal
General application	Museums & Galleries, Retail
Operating temperature range (°C)	25°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2544
Luminaire efficacy (lm/W)	62
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	97
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Distribution type	Symmetric
Photobiological Risk Group	RG0

Electrical data

Emergency type	
Total power consumption (W)	41
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	1
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	1050
Inrush Current (A)	30
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	12
Max. products per 16A C Breaker	32
Max. products per 20A C Breaker	38
Max. products per 10A B Breaker	12
Max. products per 16A B Breaker	20

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK02
Diffuser finish	Bezel (or Ring)
Diffuser material	Glass
Reflector finish	Not Applicable
Nominal Product Width (mm)	165
Nominal Product Height (mm)	200
Nominal Product Diameter (mm)	114
Weight (kg)	1.7

Beacon XL Muse 3000K DALI L3 ST Adaptor White

Item No: 2692777

Concord

Packaging

Product EAN number	5025768927777
Packaging single length / height (cm)	25.0
Packaging single width (cm)	19.5
Packaging single depth (cm)	20.0
DUN14 (inner)	05025768927777
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	19.5
Packaging outer depth (cm)	20.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	25-25
Dry applications use only	Yes